



used for: D-SUB

(b) (c) 9pos.

(b) (c) 15-37pos.

| No. of pos. | A    | B     | C    | D     | E    | F    | Part No. Bulk package | Part No. Single package |
|-------------|------|-------|------|-------|------|------|-----------------------|-------------------------|
| 9           | 34.0 | 25.00 | 25.0 | 27.75 | 14.5 | 8.5  | 165X10139X            | 165X10139XE             |
| 15          | 42.3 | 33.30 | 37.0 | 39.75 | 14.5 | 10.0 | 165X10149X            | 165X10149XE             |
| 25          | 56.0 | 47.04 | 37.0 | 39.75 | 14.5 | 10.5 | 165X10159X            | 165X10159XE             |
| 37          | 72.5 | 63.50 | 37.0 | 39.75 | 14.5 | 10.5 | 165X10169X            | 165X10169XE             |

(b) (c) NOTES:

- HOOD: POLYAMID + GF / BLACK
- JACKSCREW: BRASS; NICKEL PLATED
- STRAIN RELIEF: STEEL; NICKEL PLATED
- STRAIN RELIEF: STEEL; NICKEL PLATED
- PAN-HEAD SCREW: STEEL; NICKEL PLATED
- COUNTERSUNK-HEAD SCREW: BRASS; NICKEL PLATED

Directive 2002/95/EC RoHS compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND

| tolerance |             | dim. in mm   |               |
|-----------|-------------|--------------|---------------|
| 2011      | date        | name         |               |
| drawn     | 08.01.      | Lehmenkühler |               |
| appd.     | 08.01.      | Kühle        |               |
| 2 x d     | Ä3961       | 06.04.2011   | K.H. norm     |
| 4 x c     | Ä3418       | 31.08.2009   | Lehmen. d-old |
| 5 x b     | Ä3405       | 19.08.2009   | Lehmen.       |
| a         | Original    |              |               |
| rev.      | description | date         | name          |



|           |   |
|-----------|---|
| scale:    | 1:1   |
| material: | SEE NOTES   |
| title:    | PLASTIC HOOD<br>9-37pos.<br>straight cable exit , jack screws |
| dwg no:   | 16K1A1078   |
| part no:  | SEE TABLE   |

DIN-A  
4  
sh: 1/1