

Printed-circuit board connector - MC 1,5/ 3-GF-5,08 BK - 1729124

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Header, Nominal current: 8 A, Number of positions: 3, Pitch: 5.08 mm, Color: black, Contact surface: Tin



Key commercial data

Packing unit	1 pc
Minimum order quantity	50 pc
Weight per Piece (excluding packing)	2.27 GRM
Custom tariff number	85366990
Country of origin	Germany

Technical data

Dimensions

Pitch	5.08 mm
Dimension a	10.16 mm

General

Range of articles	MC 1,5/...GF
Rated voltage (III/3)	250 V
Connection in acc. with standard	EN-VDE
Nominal current I_N	8 A
Color	black
Number of positions	3

Classifications

eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27260704
eCl@ss 7.0	27440402
eCl@ss 8.0	27440402

Printed-circuit board connector - MC 1,5/ 3-GF-5,08 BK - 1729124

Classifications

ETIM

ETIM 3.0	EC001121
ETIM 4.0	EC002637
ETIM 5.0	EC002637

UNSPSC

UNSPSC 6.01	30211810
UNSPSC 7.0901	39121409
UNSPSC 11	39121409
UNSPSC 12.01	39121409
UNSPSC 13.2	39121409

Approvals

Approvals


Approvals


UL Recognized / cUL Recognized / CSA / VDE Gutachten mit Fertigungsüberwachung / GOST / CCA / IECCEB CB Scheme / cULus Recognized

Ex Approvals

Approvals submitted

Approval details


UL Recognized 		
	B	D
Nominal current I _N	8 A	8 A
Nominal voltage U _N	300 V	300 V

cUL Recognized 		
	B	D
Nominal current I _N	8 A	8 A


Printed-circuit board connector - MC 1,5/ 3-GF-5,08 BK - 1729124

Approvals


	B	D
Nominal voltage UN	300 V	300 V

CSA 

	B	D
Nominal current IN	8 A	8 A
Nominal voltage UN	300 V	300 V


VDE Gutachten mit Fertigungsüberwachung 

Nominal current IN	8 A
Nominal voltage UN	250 V


GOST 

CCA

Nominal current IN	8 A
Nominal voltage UN	250 V

IECEE CB Scheme 


Nominal current IN	8 A
Nominal voltage UN	250 V

cULus Recognized 

Drawings

Printed-circuit board connector - MC 1,5/ 3-GF-5,08 BK - 1729124

Diagram



Type: MC 1,5/...-STF-5,08 with MC 1,5/...-GF-5,08